



Date of issue : 11/03/2010

Last. mod. date : 26/03/2010

**Product code****04998 RI-JET 50 CAST GLOSS WHITE AIRFLOW REPOSITIONABLE ASP 33 GREY V****Description**

White gloss CASTvinyl film.

Solvent and eco-solvent ink-jet printing. The RI-JET series of ink jet print media give excellent print results with UV ink-jet printing. Testing for suitability between media, printers and inks is always recommended prior to use.

Repositionable permanent adhesive, with low tack.

Vehicle applications and advertising and promotional indoor/outdoor applications.

**Technical data****FACE MATERIAL**

Type	Cast vinyl
Colour and Finish	Gloss white
Weight	70g/m <sup>2</sup>
Thickness	50μ

**ADHESIVE**

Reference	ASP 33 permanente repositionable GREY
Type	Permanent repositionable
Min. Appl. Temp.	+10°C
Service Temp.	-20°C/120°C
Shear	High
Tack FTM9	4N/inch <sup>2</sup>
FinAdh FTM2	14N/inch

**RELEASE BACKING**

Type	Embossed PE kraft
Colour and Finish	White
Weight	160g/m <sup>2</sup>
Thickness	190μ

**Storage**

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.

The area must be dry and clean. Please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

All values presented in pdf data sheet are typical. Ritrama's data sheets provide only the general characteristics of the Product. It is the responsibility of the Customer and/or End User to determine that the Product is fit for the purpose for which the Customer and/or End User wish to use it. Ritrama can give no guarantee beyond the information given in the data sheet.