



Digital Product Range

Spec. No. : D013
Date of Issue : 10/03/03
Supersedes: None

Product Code	-	Ri-Jet 100 Perm. Blackout
Adhesive Reference	-	RI-AP + Blackout pigment
Description	-	Gloss white soft vinyl

Face Material

Caliper	-	100	microns (+/-10%)
Substance	-	140	gsm (+/-10%)
Shrinkage	-	<1%	
Recommended Life	-	3*	years
Recommended Shelf Life (Prior to printing)	-	6	months

Adhesive

Adhesive Type	-	Repositionable acrylic	
Tack	-	Medium	
Resistance to Sunlight	-	Very Good	
Minimum Application Temperature	-	+ 5°C	
Service Temperature	-	-30 to +80°C	
Cohesive Strength	-	High	
Initial Adhesion	-	900	g/25mm
Adhesion at 48 Hours	-	1800+	g/25mm

Release Liner

Type of Backing	-	Kraft - Clay ctd ss siliconised (ptd grey)	
Colour	-	White	
Substance	-	140	gsm (+/-10%)
Caliper	-	150	microns (+/-10%)

Typical Applications: Solvent inkjet printing, e.g. Vutek, Scitex, Arizona, Nur. Additional testing required for electrostatic printers, or 'eco-solvent' machines, i.e. 'Resolve'. High opacity offered due to black pigment.
*Relates to life of vinyl, life of print depends on inks used.

Available widths: 1.0/1.4/1.55 + Arizona format