



Date of issue: 05/01/2005
Last mod. date: 05/01/2005

Product Code

RI - 110 / 145 ASP8A

Description

Embossed vinyl film with excellent outdoor and abrasion resistance.

As a rule it is not printed.

Permanent adhesive with high adhesion and shear at high temperature too. Suitable for outdoor applications. Not suitable for apolar substrates (PE,PP).

For decoration and lining in the automotive industry.

Technical Data

FACE MATERIAL

Type	Plasticised polymeric PVC
Colour and Finish	Black embossed matt
Weight	150 g/m
Thickness	145 µ

ADHESIVE

Reference	RI-ASP8A
Type	Permanent acrylic (solvent based)
Min. Appl. Temp.	+5 °C
Service Temp.	-30 °C+140 °C
Cohesion	Very high
Tack	Medium
Ultimate Adhesion	Very high

RELEASE BACKING

Type	1 side silicone coated 2 side PE coated kraft
Colour and Finish	White
Weight	144 g/m
Thickness	166 µ
Transparency	0 %

CHEMICAL RESISTANCE

Detergenti	No effect (24 Hrs)
Benzine	No effect (1 Hrs)
SAE20 Motoroil	No effect (24 Hrs)
10% HCL	No effect (10 min)
10% NH4OH	No effect (10 min)

Storage

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.

The area must be dry and clean. Please keep the material in the original packaging when not use in order to protect it from dust and contaminations.

All values presented in this data sheet are typical. The information is given in good faith but without warranty. Purchasers should carefully assess the suitability of the product for their own specific application. All specifications are subject to change without prior notice.

