



Ritrama UK Limited  
 Lynwell Road  
 Lyntown Trading Estate  
 Eccles  
 Manchester  
 M30 9QG  
 UK  
 Phone: +44 (0)161 786 1760  
 Fax: +44 (0)161 786 1761

**TECHNICAL SHEET**

Date of issue: 24/06/2003

**SANDBLAST VINYL GREY**

**Product code:** CSMG  
**Description:** 300µ soft vinyl, especially designed for marble and stone high pressure sand blasting.  
**Size:** 122cm x 25m

<b>TECHNICAL DATA</b>			
<b><u>FACE MATERIAL</u></b>		<b><u>ADHESIVE</u></b>	
Type	Plasticized vinyl film	Reference	ASP8A
Colour and finish	Grey	Type	Permanent acrylic (solvent based)
Caliper	300µ	Min.appl.Temp.	+ 5° C
Substance	400g/sqm	Service temp.	- 20° C/+80° C
Shrinkage	1% - 2%	Cohesion	Excellent
		Tack	Medium
		Ultimate adhesion	Very high
<b><u>RELEASE BACKING</u></b>		<b><u>CHEMICAL RESISTANCE</u></b>	
Type	1 side silicone coated board	Detergent	No effect (24H)
Colour	white	Gasoline	No effect (1 H)
Substance	140g/sqm	SAE20 Motoroil	No effect (24 H)
Caliper	150µ	10% HCl	No effect (10min)
		10% NH4OH	No effect (10min)

All value presented in this data sheet are typical. The information is given in good faith but without warranty.