

Digital Product Range

1
2
3
4
5

Spec. No. D007
Date of Issue : 23-03-01
Supersedes : Draft

Product Code : DS Ultracrystalline

Description : Ultra clear double side adhesive coated PP with 2 PET liners.

1 :	Release	30μ Gloss Clear Polyester
2 :	Adhesive Ref : Adhesive Type :	RI-ASP5 Permanent solvent acrylic
	Tack :	Medium
	Resistance to Sunlight :	V Good
	Minimum Application Temperature :	+5°C
	Service Temperature :	-30 to +120°C
	Cohesive Strength :	V good
	Initial Adhesion :	1000
	Adhesion at 48 hours :	1400
3 :	Carrier:	30μ Gloss Clear Polypropylene
4 :	Adhesive Ref : Adhesive Type :	RI-ASP5 Permanent solvent acrylic
	Tack :	Medium
	Resistance to Sunlight :	V Good
	Minimum Application Temperature :	+5°C
	Service Temperature :	-30 to +120°C
	Cohesive Strength :	V good
	Initial Adhesion :	1000
	Adhesion at 48 hours :	1400
5 :	Release :	30μ Gloss Clear Polyester

Typical Application : Digital / photographic print mounting tape.

Widths: 1.05, 1.31, 1.50m

Digital Product Range

1
2
3
4

Spec. No. D008
Date of Issue : 23-03-01
Supersedes : Draft

Product Code : Mono-Tape 950 P

Description : Self-wound double side adhesive PET with single kraft release.

1 :	Release:	2 side siliconised 90gsm kraft
2 :	Adhesive Ref : Adhesive Type :	RI-ASP5 Permanent solvent acrylic
	Tack :	Medium
	Resistance to Sunlight :	V Good
	Minimum Application Temperature :	+5°C
	Service Temperature :	-30 to +120°C
	Cohesive Strength :	V good
	Initial Adhesion :	1000
	Adhesion at 48 hours :	1400
3 :	Carrier:	12µ Gloss Clear Polyester
4 :	Adhesive Ref : Adhesive Type :	RI-ASP5 Permanent solvent acrylic
	Tack :	Medium
	Resistance to Sunlight :	V Good
	Minimum Application Temperature :	+5°C
	Service Temperature :	-30 to +120°C
	Cohesive Strength :	V good
	Initial Adhesion :	1000
	Adhesion at 48 hours :	1400

Typical Application : Digital / photographic print mounting tape.

Widths: 1.05, 1.31, 1.53m