

Visual Communication - RI-Mark

Issue date : 23/03/2009
Date last modification : 17/02/2011**05126 ETCH GLASS PTA AIRFLOW SILVER TRANSLUCENT ASP 26 permanent WKPE 160****Face Material**

Polymeric translucent vinyl with silver metallic flakes.

Type	Polymeric vinyl with metallic flakes		
Colour and Finish	Silver translucent		
Weight	100 g/m ² ±10%	ISO 536	
Thickness	80 µ ±10%	ISO 534	

Adhesive

Acrylic permanent solvent based adhesive.

Reference	ASP26 with Air Flow liner		
Type	Permanent acrylic (solvent based)		
Min. Appl. Temp.	+10°C		
Service Temp.	+10°C/+120°C		
Shear	Medium		
Tack	6 N/inch ²	FINAT FTM9	
Final Adhesion	12 N/inch	FINAT FTM2	

Liner

Type	2 sides PE coated 1 side siliconised embossed		
Colour and Finish	White		
Weight	160 g/m ² ±10%	ISO 536	
Thickness	190 µ ±10%	ISO 534	

Applications

Suitable for 5 years outdoor applications. Size available: h 1220/1520 mm X 50 m.

Printing Methods

As a rule it is not printed.

Shelf lifemonths, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

