

Ri-Mark Series

Spec. No.: RM10
Date of Issue : 16-05-00
Supersedes: Draft

Glass Etch PTA Available Colours: 3

80µ Soft Vinyl - matt 'etch' finish

Face Material	Face Caliper:	80µ
	Weight:	110 gsm
	Film Type:	Polymeric
	Dimensional Stability (DIN 53479):	<0.5%
	Conformability:	Excellent
	Flammability (DIN 752000):	Self Extinguishing
	Resistance against chemicals and solvents (DIN 51958):	
	- Distilled water/32°C @ 150 hours	- No change
- Diesel oil / normal climate @ 24 hrs	- No change	
- Hydraulic oil / normal climate @ 24 hours	- No change	
- Cold cleaning agent mixture @ 8 hours	- No change	
- Soap / 65°C @ 8 hours	- No change	

Adhesive	Adhesive Code:	RI-ASP8
	Adhesive Type:	Permanent Acrylic
	Resistance to Sunlight:	Excellent
	Tack:	Medium
	Cohesive Strength:	Very high
	Min Application Temp.:	+10°C
	Service Temp.:	-30 to +80°C
	Initial Adhesion to SS:	1300 g/25 mm
48 Hr Adhesion to SS:	1800 g/25 mm	

Release	Release type:	Kraft - single side siliconised
	Colour:	White
	Backprint:	Plain
	Release Weight:	140 gsm
	Release Caliper:	150µ

Available Width: **1.22m**

Typical Usages: Window etch effect. Available in standard finish, blue and green.