



Ritrama S.p.A. Caponago Tel. +39 02 955 459 1
info@ritrama.it
Ritrama S.p.A. Fabriano Tel. +39 0732 97061
info@ritrama.it
Ritrama Ltd.(UK) Tel. +44 161 786 1760
sales@ritrama.co.uk
Coating Ricofin S.r.l. Tel. +39 02 9210 6310
info@ricofin.it

Ritrama S.A. Tel +34 93 729 4998
info@ritrama.es
Ritrama Inc. Minneapolis (USA) Tel. +1 612 378 2277
rdi@ritrama.com
Ritrama Inc. Cleveland (USA) Tel. +1 216 851 2300
rdi@ritrama.com
Web site: www.ritrama.com

Date of issue: 17-03-2006

TECHNICAL SHEET

RI JET 75 PE CLEAR

Product code: RI JET 75 PE CLEAR

Description: Gloss Clear polymeric soft vinyl allowing long term application even on slightly corrugated surfaces, the double side PE make good stability.
Media specifically developed for and widely used with the following machines: Scitex, Grandjet S Series, Idanit 162; PressJet, XLJet; Vutek UltraVu Series; NUR Fresco, Blueboard, Slasa Series, Oce Arizona Series; MutohAlbatross; Mimaki JV3, JV4; Durst Rho; ZÜnd Uvjet 215C, Inca Eagle 44, Digidelta SPJ4, SPJM4. Also suitable for use with: DGI, Signjet, Yaselan, Techwin & Flora, Roland Versacam.
Specifically designed for LFDP.

Size available: h 1370 -1400 - 1520 - 1550mm x 50 - 100 m

TECHNICAL DATA

<u>FACE MATERIAL</u>		<u>ADHESIVE</u>	
Type	Polymeric Soft vinyl	Reference	ASP 26
Colour and finish	Gloss, clear	Type	Permanent acrylic (solvent based)
Caliper	75 μ \pm 10%	Min. appl. temp.	+ 10°C
Substance	97 g/sqm \pm 10%	Service temp.	-20°C to +120°C
<u>RELEASE BACKING</u>		Cohesion	High
Type	1 side siliconised, 2 side PE coated Kraft paper	Tack	Medium
Colour	white	Ultimate adhesion	> 15 N/Inch
Substance	144 g/sqm \pm 10%	<u>CHEMICAL RESISTANCE</u>	
Caliper	150 μ \pm 10%	Detergent	No effect (24 Hrs)
		Gasoline	No effect (1 Hr)
		SAE20 Motoroil	No effect (24 Hrs)
		10% HCl	No effect (10 min)
		10% NH4OH	No effect (10 min)

All values presented in this data sheet are typical. The information is given in good faith but without warranty.