



Ritrama S.p.A. Monza Tel. +39 039 839215
info@ritrama.it
 Ritrama S.p.A. Fabriano Tel. +39 0732 97061
info@ritrama.it
 Ritrama Ltd.(UK) Tel. +44 161 786 1760
sales@ritrama.co.uk
 Coating Ricofin S.r.l. Tel. +39 02 9210 6310
info@ricofin.it

Ritrama S.A. Tel +34 93 729 4998
info@ritrama.es
 Ritrama Inc. Minneapolis (USA) Tel. +1 612 378 2277
rdi@ritrama.com
 Ritrama Inc. Cleveland (USA) Tel. +1 216 851 2300
rdi@ritrama.com

Web site: www.ritrama.com

Date of issue: 16-02-2004

TECHNICAL SHEET

RI Jet 75 White

Product code: RI JET 75 white

Description: Gloss white polymeric soft vinyl allowing long term application even on slightly corrugated surfaces.
 Media specifically developed for and widely used with the following machines: Scitex, Grandjet S Series, Idanit 162; PressJet, XLJet; Vutek UltraVu Series; NUR Fresco, Blueboard, Slasa Series, Oce Arizona Series; MutohAlbatross; Mimaki JV3, JV4; Durst Rho; ZÜnd Uvjet 215C, Inca Eagle 44, Digidelta SPJ4, SPJM4. Also suitable for use with: DGI, Signjet, Yaselan, Techwin & Flora, Roland Versacam. **Specifically designed for LFDP.**

Size available: h 1400 – 1550 mm x 50 -100 m

TECHNICAL DATA

<u>FACE MATERIAL</u>		<u>ADHESIVE</u>	
Type	Polymeric soft vinyl	Reference	RI-ASP 26
Colour and finish	Gloss, white	Type	Permanent acrylic (solvent based)
Caliper	75 µ ±10%	Min. appl. temp.	+ 10 °C
Substance	100 g/sqm ±10%	Service temp.	-20 °C to + 120 °C
		Shear s. s. FTM-8	> 50h
		Quick Stick on glass FTM-9	10±1 N/Inch ²
		Ultimate adhesion FTM-1	> 18 N/Inch
<u>RELEASE BACKING</u>		<u>CHEMICAL RESISTANCE</u>	
Type	1 side siliconised Bipe	Detergent	No effect (24 Hrs)
Colour	white	Gasoline	No effect (1 Hr)
Substance	144 g/sqm ±10%	SAE20 Motoroil	No effect (24 Hrs)
Caliper	150 µ ±10%	10% HCl	No effect (10 min)
		10% NH4OH	No effect (10 min)

All values presented in this data sheet are typical. The information is given in good faith but without warranty.