



## Digital Product Range

Spec. No. : D012  
Date of Issue : 25/07/2006  
Supersedes: 25/07/2006

<b>Product Code</b>	-	Ri-Jet 100 Blackout
Adhesive Reference	-	RI-AVM + BO
Description	-	Gloss white soft vinyl

### Face Material

Caliper	-	100	microns (+/-10%)
Substance	-	140	gsm (+/-10%)
Shrinkage	-	<1%	
Recommended Life	-	3*	years
Recommended Shelf Life (Prior to printing)	-	6	months

### Adhesive

Adhesive Type	-	Semi-permanent + blackout	
Tack	-	Medium	
Resistance to Sunlight	-	Very Good	
Minimum Application Temperature	-	+ 5°C	
Service Temperature	-	-30 to +100°C	
Cohesive Strength	-	High	
Initial Adhesion	-	500	g/25mm
Adhesion at 48 Hours	-	800	g/25mm

### Release Liner

Type of Backing	-	Kraft - Clay ctd ss siliconised	
Colour	-	White	
Substance	-	140	gsm (+/-10%)
Caliper	-	150	microns (+/-10%)

**Typical Applications:** Solvent inkjet printing e.g. Vutek, Scitex, Arizona, Nur. High opacity offered due to black pigment. \*Relates to life of vinyl, life of print depends on inks used. Vinyl is self-extinguishing.

**Available widths:** 1.4/1.55 + Arizona format