



Ritrama UK Limited
 Lynwell Road
 Lyntown Trading Estate
 Eccles
 Manchester
 M30 9QG
 UK
 Phone: +44 (0)161 786 1760
 Fax: +44 (0)161 786 1761

TECHNICAL SHEET

Date of issue: 24/06/2003

SANDBLAST VINYL GREY

Product code: CSMG
Description: 300µ soft vinyl, especially designed for marble and stone high pressure sand blasting.
Size: 122cm x 25m

TECHNICAL DATA			
<u>FACE MATERIAL</u>		<u>ADHESIVE</u>	
Type	Plasticized vinyl film	Reference	ASP8A
Colour and finish	Grey	Type	Permanent acrylic (solvent based)
Caliper	300µ	Min.appl.Temp.	+ 5° C
Substance	400g/sqm	Service temp.	- 20° C/+80° C
Shrinkage	1% - 2%	Cohesion	Excellent
		Tack	Medium
		Ultimate adhesion	Very high
<u>RELEASE BACKING</u>		<u>CHEMICAL RESISTANCE</u>	
Type	1 side silicone coated board	Detergent	No effect (24H)
Colour	white	Gasoline	No effect (1 H)
Substance	140g/sqm	SAE20 Motoroil	No effect (24 H)
Caliper	150µ	10% HCl	No effect (10min)
		10% NH4OH	No effect (10min)

All value presented in this data sheet are typical. The information is given in good faith but without warranty.