



Date of issue : 05/01/2005
Last. mod. date : 16/03/2009

Product code

01228 ULTRACRYSTALLINE Perm/Perm PP CLEAR ASP 8A permanent PET 30

Description

Optically clear double side tape to be used where ultra transparency is required.

Not printable.

Permanent adhesive with high adhesion and shear at high temperature too. Suitable for outdoor applications. Not suitable for apolar substrates (PE,PP).

For applications on windows, glass, clear boards, etc.

FACE MATERIAL

Type	Top coated polypropylene
Colour and Finish	Clear, gloss
Weight	27 g/m ²
Thickness	30 μ

ADHESIVE

Reference	AP 906
Type	Acrylic permanent
Min. Appl. Temp.	+10°C
Service Temp.	-40°C/+140°C
Shear	Very high
Tack FTM9	15 N/inch ²
FinAdh FTM2	7 N/inch

RELEASE BACKING

Type	1 side siliconised polyester
Colour and Finish	Clear
Weight	46 g/m ²
Thickness	30 μ
Transparency	>95 %

Storage

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.

The area must be dry and clean. Please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

All values presented in this data sheet are typical. Ritrama's data sheets provide only the general characteristics of the Product. It is the responsibility of the Customer and/or End User to determine that the Product is fit for the purpose for which the Customer and/or End User wish to use it. Ritrama can give no guarantee beyond the information given in the data sheet.

Ritrama S.p.A.
Ritrama S.p.A. Sassoferrato
Coating Ricofin S.r.l.
Ritrama S.A.
Ritrama Ltd.(UK)
Ritrama Inc. Minneapolis (USA)
Ritrama Inc. Cleveland (USA)

Tel. +39 02 955 459 1
Tel. +39 0732 97061
Tel. +39 02 955 430 1
Tel. +34 93 729 49 98
Tel. +44 161 786 1760
Tel. +1 612 378 2277
Tel. +1 216 851 2300

info@ritrama.it
info@ritrama.it
info@ricofin.it
ritrama@ritrama.es
sales@ritrama.co.uk
info@ritrama.com
info@ritrama.com

