



COATING RICOFIN S.r.l  
Via Brescia 47A  
20063 CERNUSCO S/NAVIGLIO (MI) Italy  
☎+39 02 92106310 r.a. FAX +39 02 92102459  
e-mail : info@ricofin.it  
C.FISC./P.IVA IT 09152050150

Date of issue: 28/03/05

**PROVISIONAL**

**TECHNICAL SHEET**

**GLOSS CLEAR OVERLAMINATING POLYESTER**

**Product code:** C 1030 RI-6481 ANTIGRAFFITI

**Description:** Polyester ANTIGRAFFITI System with very good transparency (low haze) and with UV screening characteristics. Not printable. Permanent acrylic adhesive with excellent performance even at extreme outdoor conditions, and with very high UV protection characteristics.  
For applications where the best UV resistance is required and where is necessary to protect from vandals action

**TECHNICAL DATA**

<u>FACE MATERIAL</u>		<u>ADHESIVE</u>	
Type	LH polyester with ANTIGRAFFITI System	Reference	RI ASP8-A
Colour and finish	Clear, Gloss	Type	Permanent acrylic (solvent based) with UV protection
Caliper	30 µ ±10%	Min. appl. temp.	+10 °C
Substance	28 g/sqm ±10%	Service temp.	-10 °C to +110 °C
Shrinkage	0 %	Cohesion	High
		Tack	Medium
		Ultimate adhesion	High
<u>RELEASE BACKING</u>		<u>CHEMICAL RESISTANCE</u>	
Type	1 side siliconised Polyester	Detergent	No effect (24H)
Colour	Clear	Gasoline	No effect (1 H)
Substance	46 g/sqm ±10%	SAE20 Motoroil	No effect (24 H)
Caliper	30 µ ±10%	10% HCl	No effect (10min)
		10% NH4OH	No effect (10min)

All values presented in this data sheet are typical. The information is given in good faith but without warranty.