



Date of issue : 15/10/2008

Last. mod. date : 10/02/2009

Product code

03355 RI-MARK TRANSLUCENT SERIES

Description

Self adhesive material for plotter. Polymeric matt finish vinyls, suitable for 5/7 years outdoor use. 21 colours available.

Printable in solvent and UV screenprinting.

Permanent solvent acrylic, with excellent water resistance allowing wet applications.

For illuminated signs and window graphics.

Technical data

FACE MATERIAL

| | |
|-------------------|------------------------------|
| Type | Plasticised polymeric vinyls |
| Colour and Finish | 21 available colours |
| Weight | 106g/m ² |
| Thickness | 90µ |

ADHESIVE

| | |
|-------------------|-------------------|
| Reference | RI - ASP26 |
| Type | Acrylic Permanent |
| Min. Appl. Temp. | +10°C |
| Service Temp. | -20°C / +120°C |
| Shear | High |
| Tack | Medium |
| Ultimate Adhesion | High |

RELEASE BACKING

| | |
|-------------------|------------------------------|
| Type | Kraft 1 side silicone coated |
| Colour and Finish | White |
| Weight | 120g/m ² |
| Thickness | 120µ |

CHEMICAL RESISTANCE

| | |
|----------------|--------------------|
| Detergent | No effect (24 Hrs) |
| Gasoline | No effect (1 Hrs) |
| SAE20 Motoroil | No effect (24 Hrs) |
| 10% HCl | No effect (10 min) |
| 10% NH4OH | No effect (10 min) |

Storage

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.

The area must be dry and clean. Please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

All values presented in pdf data sheet are typical. Ritrama's data sheets provide only the general characteristics of the Product. It is the responsibility of the Customer and/or End User to determine that the Product is fit for the purpose for which the Customer and/or End User wish to use it. Ritrama can give no guarantee beyond the information given in the data sheet.