



Date of issue : 23/03/2009

Last. mod. date : 19/04/2010

Product code

05126 ETCH GLASS PTA AIRFLOW SILVER TRANSLUCENT ASP 26 permanent WK

Description

Polymeric translucent vinyl with silver metallic flakes.

As a rule it is not printed.

Acrylic permanent solvent based adhesive.

Suitable for 5 years outdoor applications. Size available: h 1220/1520 mm X 50 m.

Technical data

FACE MATERIAL

Type	Polymeric vinyl with metallic flakes
Colour and Finish	Silver translucent
Weight	100g/m ²
Thickness	80μ

ADHESIVE

Reference	ASP26 with Air Flow liner
Type	Permanent acrylic (solvent based)
Min. Appl. Temp.	+10°C
Service Temp.	+10°C/+120°C
Shear	Medium
Tack FTM9	6N/inch ²
FinAdh FTM2	12N/inch

RELEASE BACKING

Type	2 sides PE coated 1 side siliconised embossed
Colour and Finish	White
Weight	160g/m ²
Thickness	190μ

Storage

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.

The area must be dry and clean. Please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

All values presented in pdf data sheet are typical. Ritrama's data sheets provide only the general characteristics of the Product. It is the responsibility of the Customer and/or End User to determine that the Product is fit for the purpose for which the Customer and/or End User wish to use it. Ritrama can give no guarantee beyond the information given in the data sheet.