GRAPHTEC

Cutting Plotter CE7000-40 / CE7000-60 / CE7000-130 / CE7000-160

Enhanced performance & specification at an unrivalled price point

Features fast cutting speed of up to 1000mm/s and a cutting force of 450g

Ease of use with enhanced media tracking capabilities

ARMS 8.0 optical print and cut detection system

Cut mulitple pre-printed graphics without user input by using the latest barcode technology

Includes high quality, easy to use, professional grade Graphtec Pro Studio software.

* The basket in photo above is optional item

www.graphtecgb.co.uk

Graphtec, the brand that never stops evolving!

Incorporating new features traditionally only found on higher level more expensive cutting plotters, the CE7000 series offers unrivalled value for money.



4 sizes available to suit your needs

From the compact 400mm desktop option to the new wide format 1.6M, the CE7000 series has a size to suit every application.

	Media
CE7000-160	← 1626mm
CE7000-130	←1372mm>
CE7000-60	← 712mm
CE7000-40	← 484mm →

Supports various cutting patterns such as perforation cut with maximum cutting force 450g and maximum cutting speed 1000mm/s



[Carrier Sheet Table]

It is an optional item that can be attached to the

front and back of the cutting plotter to support

a carrier sheet.

* Available with CE7000-40 / -60.

Performance that guarantees accurate long length tracking

The media stocker helps stabilize the feeding of media. By adjusting the pressure of the middle push roller to the media (* 1) in three levels, it prevent media floating.

Secer

Additionally, by using an optional special basket, stability of long cuts can be achieved.





Push roller pressure switching (CE7000-130/160)

Data output via USB flash memory without PC

The cutting data designed with Cutting Master 4 or Graphtec Pro Studio / Plus can be output directly to the cutting plotter by saving to USB flash memory. This simplified work-flow enables users to operate without a computer.

* The USB memory format only supports FAT32. Please note that NTFS and exFAT are not supported









Software

Graphtec Pro Studio Standard Accessory **Graphtec Studio**



Adobe Illustrator / CorelDRAW plug-in software

Cutting Master 4

000 Solid fil oke Edit \$ 1 0 -¥ 0.200mm

Cutting Master 4 is Graphtec plug-in software for Adobe Illustrator and CoreIDRAW Graphic Suite. It sends cutting data to the plotter and includes a variety of functions such as: preview, registration mark ions, cut job settings and more. Cutting Master 4 is easy to use and enables you to get the best performance from your

		u		
S (*4)	Windows 10/8.1/7, Mac OS X 10.7~macOS 10.15			
)	Adobe Illustrator : CC2019/CC2018/CC2017/CC2015.3/CC2015/CC2014/CC/CS6/CS5/CS4 (*5) CoreIDRAW : Graphics Suite 2019/2018/2017/X8/X7/X6/X5/X4	S		
ures>		</td		
cpanc	l, shrink the object directly from the preview window	•		
bject outline, recognize the line width and overlap				
nu lavar ar salar 🗖 lasart waading line				

 Outp o small pieces with tilling funct

<Main Fe

Move

o be imported into the software phtec Pro Studio | Windows10/8.1/7 phtec Studio Mac OS X 10.6~macOS 10.15

Create designs using auto-shape, various line types, etc. Texts edit (rotate, mirror, fit-to-shape, etc.)

Auto-trace (supporting bmp, tiff, jpeg, gif, etc. image format) Connectable and switchable to multiple plotters

EPS, DXF format files and other raster format files are supported ● Layer (*6) ● Output by color ● Insert weeding line (*6)

ARMS 8.0

Data Link Function (Barcode Data Management/Continuous Cutting)

By reading the Graphtec original Barcode, CE7000 automatically detects its linked data from PC or USB flash memory. This function is available regardless of which printer or RIP software is used.



Continuous Cut (Data Link function)

Barcode data management allows cutting different data sequentially by detecting the "Start Mark" of the new Barcode. Sequential Print & Cut process with roll-media is now available.



Supports colored marks / specialty media

A wide variety of media types including holographic paper and reflective sheets are now compatible due to improvements of the ARMS sensor algorithm.

Ex. * Sensor may not be able to read certain combinations of specialty media and colored marks.



Expanded Cutting Area

The expanded cutting area to include objects outside of the area enclosed by registration marks. Production efficiency is enhanced by reducing media waste.



Optional basket (CE7000-60/130/160)

Media stocker (CE7000-60/130/160)









<Main Features of Graphtec Pro Studio Plus for Rhinestor

Rhinestone design support

<Main Features of Graphtec Pro Studio Plus for Auto Nesting>

Nesting (Auto, Power Nest, intelligent)

Supports Adobe Illustrator "Crop Marks"

Using the plug-in software Cutting Master 4, Adobe Illustrator crop marks will be available.



Specifications							
ltem		CE7000-40		CE7000-60	CE7000-130	CE7000-160	
Configuration		Grit rolling type					
Drive method		Digital servo dri	ve				
Max. cutting area (W	V x L) (*1)	375mm × 50m		603mm × 50m	1270mm × 50m	1524mm × 50m	
Cutting area of guaran	teed accuracy (*1)	355mm× 2m		583mm × 2m	1250mm × 2m	1504mm × 2m	
(When using option	al basket)			(583mm × 5m)	(1250mm × 5m)	(1504mm × 5m)	
Mountable	Min.	50mm					
media width	Max.	484mm (19inch)	712mm (28inch)	1372mm (54inch)	1626mm (64inch)	
Mountable roll med		5kg		9kg	17kg	20kg	
Number of push roll	lers			4 rollers (Max. 5 (option))			
Max. cutting speed				1000mm/s at 45° direction			
Acceleration		Max. 21.2m/s ² at 45° direction Max. 13.9m/s ² at 45° direction					
Cutting force		Max. 4.41N (450					
Minimum character		Approx. 5 mm alphanumeric (varies depending on character font and media)					
Mechanical resolution	on	0.005mm					
Programmable reso	lution	GP-GL: 0.1/0.05/0.025/0.01mm HP-GL [™] (*2): 0.025mm					
Repeatability (*1)		Max. 0.1 mm in plot up to 2 m (Excluding media expansion and contraction)					
Mountable number	of tools	1 tool					
Blade types		Supersteel					
Pen types		Oil-based ballpoint pen, Water-based fiber-tip pen					
Media types		Up to 0.25mm thickness					
Marking film (PVC / fluorescence / reflection), polyester film (With specified conditions)							
Interface	USB 2.0(Full Speed), Ethernet 10BASE-T/100BASE-TX						
Buffer memory 2MB							
Command sets				or auto-detect) (*2)			
Display		Graphic type LCD with back-light (240dots x 128dots), supports 10 languages					
Power source		100V to 120V AC, 200V to 240V AC, 50 / 60 Hz					
Power consumption		Up to 100W					
Operating environm			o 75 % R.H. (non-co				
Guaranteed accurac			o 70 % R.H. (non-co				
External dimensions	s (W x D x H)	Approx. 772 x 2	92 🗙 313 mm	Approx. 1005 × 582 × 1092 mm	Approx. 1704 × 811 × 1215 mm	Approx. 1916 × 811 × 1215 mm	
(with basket)	h basket)		(1005 × 936 × 1092 mm)(*3)	(1704 × 1148 × 1215 mm)(*3)	(1916 × 1148 × 1215 mm)(*3)		
Weight (approx.)			23 kg	51 kg	55 kg		
(with basket)				(25.2 kg)(*3)	(54.9 kg)(*3)	(59.5 kg)(*3)	
Compatible OS (*4)		Windows 10/8.1/7					
		Mac OS X 10.6 ~ 10.11 / macOS 10.12 ~ 10.15 (Graphtec Studio: 10.6 - 10.15, Cutting Master 4: 10.7 - 10.15)					
Supported software	e (*5)	Graphtec Pro Studio(Windows)(*6), Graphtec Studio(Mac), Cutting Master 4(*6), Windows Driver					
Safety		PSE, UL/cUL, CE mark					
EMC		VCCI Class A, FCC Class A, CE mark					
Option					Standard accessories		
Item		Part No.	Description			y Description	
Basket for CE7000 se	eries	PG0103	For CE7000-60		Power cord 1	The type of cord is different by destination.	

Part No.	Description	I
PG0103	For CE7000-60	
PG0104	For CE7000-130	I
PG0105	For CE7000-160	(
OPH-A45	For CE7000-40 or CE7000-60	(
OPH-A49	Only for CE7000-130/CE7000-160	
ST0118	For CE7000-60	I
OPS682-PLS	Design software including all advanced functions (1 license)	١
OPS682-RSF	Limited edition of rhinestone function only (1 license)	
OPS682-ANF	Limited edition of auto nesting function only (1 license)	1
	PG0103 PG0104 PG0105 OPH-A45 OPH-A49 ST0118 OPS682-PLS OPS682-RSF	PG0103 For CE7000-60 PG0104 For CE7000-130 PG0105 For CE7000-160 OPH-A45 For CE7000-40 or CE7000-60 OPH-A49 Only for CE7000-130/CE7000-160 ST0118 For CE7000-60 OPS682-PLS Design software including all advanced functions (1 license) OPS682-RSF Limited edition of rhinestone function only (1 license)

Supplies				
Item	Part No.	Description Package		
Cutting blade holder	PHP33-CB09N-HS	For CB09U series blade	1 set/pack	
	PHP33-CB15N-HS	For CB15U series blade	1 set/pack	
Cutting blade	CB09-P	0.9mm dia. 45º angle, Supersteel	5 blades/pack	
	CB09UB-5	0.9mm dia. 45° angle, Supersteel	5 blades/pack	
CB09UB-K6		0.9mm dia. 60° angle, for Car-film	5 blades/pack	
	CB15U-5	1.5mm dia. 45° angle, for paper/cardboard	5 blades/pack	
	CB15U-K30-5	1.5mm dia. 30° angle, for paper/cardboard	5 blades/pack	
Loupe	PM-CT-001	Checking blade length, for PHP33 and PHP35 series	1 set/pack	
Fiber-tip pen holder	PHP31-FIBER	Pen holder for KF700 series pen	1 set/pack	
Water-based	KF700-BK	Pen (black)	10 pens/pack	
fiber-tip pen	KF700-RD	Pen (red)	10 pens/pack	
Ballpoint pen holder	PHP34-BALL	Pen holder for KB700 pen	1 set/pack	
Oil-based ballpoint pen	KB700-BK	Pen (black)	10 pens/pack	
Carrier Sheet	CR09300-A3	A3 size	2 sheets/pack	
Cutting mat	PM-CR-009	For CE7000-40 replacement cutting mat	2 sets/pack	
	PM-CR-010	For CE7000-60 replacement cutting mat	2 sets/pack	
	PM-CR-011	For CE7000-130 replacement cutting mat	2 sets/pack	
	PM-CR-012	For CE7000-160 replacement cutting mat	2 sets/pack	

Standard accessories		
Item	Qty	Description
Power cord	1	The type of cord is different by destination.
USB Cable	1	2.9m long
Cutting blade holder	1	PHP33-CB09N-HS
Cutting Blade	1	CB09UB-1P
Loupe	1	PM-CT-001
Fiber-tip pen holder	1	PHP31-FIBER
Water-based Fiber-tip pen	1	KF700-BK (black)
Roll Media Tray	1	Only for CE7000-40
Stand for CE7000	1	Standard accessory for 130 / 160
DVD-ROM	1	User manual, Windows driver,
		Graphtec Pro Studio (Windows, 1 license),
		Graphtec Studio (Mac), Cutting Master4
Printed document	1	Setup Manual, Cutter Blade Manual
		and Safety Manual

CE7000-160 is not available in US & Korea. Operated with Graphtec specified cutting condition and media. *1

For long-length cutting, the basket is used. HP-GL[™] is a registered trademark of Hewlett-Packard Company. When equipped with the stand.

*2 *3 ·____

When equipped with the stand. Graphtec does not support software/driver used with operating systems that have become obsolete and are no longer supported by the OS developer. The software can be used by downloading from Graphtec website. It requires an Internet connection in order for activation or registration when starting the software for the first time. *4

*5 *6

Brand names and product names listed in this brochure are the trademarks or registered trademarks of their respective owners.
Items mentioned are subject to change without notice. For more information about product, please check the web site or contact your local representative.

Important safety instructions

Before using it, please read the user manual and then please use it properly in accordance with the description.
To avoid malfunction or electric shock, please ensure ground connection and use it in specified power source.



Graphtec GB Ltd, Nyquist House, Ellice Way, Wrexham LL13 7YT Tel: +44 1978 666700 Email:sales@graphtecgb.co.uk

Website http://www.graphtecgb.co.uk

RoHS compliant product CE7000_JE10551_1P