Technical Data Sheet

Issue date : 15/10/2008
Date last modification : 13/12/2016

GRAPHICS - RI-MARK

TRANSPARENT SERIES ASP26 PERMANENT WK120

Face Material

Self-adhesive material for plotter. Monomeric gloss finish transparent vinyl. Liner that offers superior cuttability with conventional die-cutting and computer sign making systems.

Type	Monomeric transparent vinyl	
Colour and Finish	14 colours available	
Weight	105 g/m² ±10%	ISO-536
Thickness	80 µ ±10%	ISO 534-80

Adhesive

Permanent solvent acrylic featuring high cohesion and good water resistance.

Reference	ASP26 permanent
Type	Acrylic permanent
Min. Appl. Temp.	+10°C
Service Temp.	-20°C/+130°C
Shear	High
Tack	Medium N/inch²
Final Adhesion	High N/inch

Liner

Type	One side siliconised clay coated Kraft	
Colour and Finish	White	
Weight	120 g/m² ±10%	PP-032 - ISO 536
Thickness	108 µ ±10%	ISO 534
Transparency	n.a. %	DIN 53 147-64

Applications

Coloured clear vinyl for glass decoration and light boxes. 3-5 years outdoor durability. Durability is given in good faith based on simulated weathering tests and real life vertical exposure in non-extreme mid-European conditions.

Printing Methods

Not printable.
Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following ***STORAGE CONDITIONS***:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.
All information is subject to change without prior notice.

Ritrama S.p.A.
Via Senatore Simonetta, 24
20867 Caponago (MB) ITALY
e-mail:info@ritrama.com
www.ritrama.com