

**VISCOM-RI-MARK - SOFT VINYL**

Issue date : 09/03/2012  
Date last modification : 09/03/2012

**06327 - RI-MARK L101 GLOSS BLACK AR801 REMOVABLE WK120 NEUTRAL**
**Face Material**

Self-adhesive material for plotter. Monomeric gloss finish vinyl. Liner that offers superior cuttability with conventional die-cutting and computer signmaking systems.

Type	Monomeric vinyl	
Colour and Finish	Gloss black	
Weight	95 g/m <sup>2</sup> ±10%	ISO-536
Thickness	70 µ ±10%	ISO 534-80

**Adhesive**

Acrylic removable adhesive featuring good clarity and clean removability from glass, laminated plastics and crosslinked enamels. Not suitable for application on papers, PVC and air dried paints and varnishes.

Reference	AR801	
Type	Acrylic removable	
Min. Appl. Temp.	+5 °C	
Service Temp.	-40 °C/+120 °C	
Shear	High	
Tack	2 N/25mm	FINAT FTM9
Final Adhesion	2 N/25mm	FINAT FTM2

This adhesive complies with FDA 175.105.

**Liner**

Type	One side siliconised clay coated Kraft	
Colour and Finish	White	
Weight	120 g/m <sup>2</sup> ±10%	ISO 536
Thickness	108 µ ±10%	ISO 534
Transparency	n.a. %	DIN 53 147-64

**Applications**

Temporary traffic signage or other short-term applications where easy removability is required.

**Printing Methods**

Testing for suitability between media, printers and inks is always recommended prior to use.  
Testing for suitability between media, printers and inks is always recommended prior to use.

**Shelf life**

36 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.  
All information is subject to change without prior notice.